

## PGDQ2.MH11669 Marking and Labeling Systems - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

### Marking and Labeling Systems - Component

[See General Information for Marking and Labeling Systems - Component](#)

**SERIDRUCK GMBH**  
Gossholzer Strasse 42  
88161 Lindenberg, GERMANY

MH11669

Model No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
<b>Pressure-sensitive printed labels.</b>						
<b>AF150/K2</b>						
	Acrylonitrile butadiene styrene	80	-	X	-	O
	Alkyd paint	80	-	X	-	O
	Aluminum	80	-	X	-	O
	Galvanized steel	80	-	X	-	O
	Nylon - Polyamide	80	-	X	-	O
	Polystyrene	80	-	X	-	O
	Stainless steel	80	-	X	-	O
<b>AF200/K4</b>						
	Aluminum	100	-40	X	X	O
	Acrylonitrile butadiene styrene	80	-40	X	X	O
	Alkyd paint	80	-40	X	X	O
	Epoxy	80	-40	X	X	O
	Galvanized steel	80	-40	X	X	O
	Nylon - Polyamide	80	-40	X	X	O
	Polyester paint	80	-40	X	X	O
	Polyethylene terephthalate	80	-40	X	X	O
	Polyphenylene oxide/ether	80	-40	X	X	O
	Polyurethane paint	60	-40	X	X	O
	Porcelain	60	-40	X	X	-
	Stainless steel	60	-40	X	X	O
	Polycarbonate	40	-40	X	X	O
<b>AF200/K4533, HPE20PA/K4533</b>						
	Aluminum	80	-	X	-	-
	Galvanized steel	80	-	X	-	-
	Polyester paint	80	-	X	-	-
	Stainless steel	80	-	X	-	-
	Acrylonitrile butadiene styrene	60	-	X	-	-
	Nylon - Polyamide	60	-	X	-	-
	Polycarbonate	60	-	X	-	-
	Polyvinyl chloride	60	-	X	-	-
	Unsaturated polyester - thermoset	60	-	X	-	-
<b>AL3M/R10</b>						
	Aluminum	150	-	X	-	F1, F2
	Galvanized steel	150	-	X	-	-
	Porcelain	150	-	X	-	-
	Stainless steel	150	-	X	-	F1, F2
	Alkyd paint	100	-	X	-	F1, F2
	Acrylonitrile butadiene styrene	80	-	X	-	-
<b>ED3690/M</b>						
	Acrylic paint	40	-40	X	-	O
	Acrylonitrile butadiene styrene	40	-40	X	-	O

	Alkyd paint	40	-40	X	-	O
	Nylon - Polyamide	40	-40	X	-	O
	Polycarbonate	40	-40	X	-	O
	Polyester paint	40	-40	X	-	O
	Polyphenylene oxide/ether	40	-40	X	-	O
	Polypropylene	40	-40	X	-	O
	Polyurethane paint	40	-40	X	-	O
	Zinc	40	-40	X	-	O
	Zinc plated metal with chromate	40	-40	X	-	O
<b>ED3690/R10</b>						
	Acrylic paint	60	-40	X	-	O
	Acrylonitrile butadiene styrene	60	-40	X	-	O
	Alkyd paint	60	-40	X	-	O
	Nylon - Polyamide	60	-40	X	-	O
	Polycarbonate	60	-40	X	-	O
	Polyester paint	60	-40	X	-	O
	Polyphenylene oxide/ether	60	-40	X	-	O
	Polyurethane paint	60	-40	X	-	O
	Zinc	60	-40	X	-	O
	Zinc plated metal with chromate	60	-40	X	-	O
	Polypropylene	40	-40	X	-	O
<b>MPE-K2, HPE-K2</b>						
	Acrylonitrile butadiene styrene	60	-	X	-	O
	Alkyd paint	60	-	X	-	O
	Aluminum	60	-	X	-	O
	Galvanized steel	60	-	X	-	O
	Nylon - Polyamide	60	-	X	-	O
	Polystyrene	60	-	X	-	O
	Stainless steel	60	-	X	-	O
<b>MPE-K4, HPE-K4</b>						
	Acrylonitrile butadiene styrene	80	-	X	-	-
	Alkyd paint	80	-	X	-	-
	Aluminum	80	-	X	-	-
	Galvanized steel	80	-	X	-	-
	Nylon - Polyamide	80	-	X	-	-
	Polyphenylene oxide/ether	80	-	X	-	-
	Porcelain	80	-	X	-	-
	Stainless steel	80	-	X	-	-
	Zinc phosphated steel	80	-	X	-	-
	Polycarbonate	60	-	X	-	-
	Polyester paint	60	-	X	-	O
<b>MPE13PK/K2</b>						
	Acrylonitrile butadiene styrene	80	-	X	-	-
	Alkyd paint	80	-	X	-	-
	Aluminum	80	-	X	-	-
	Galvanized steel	80	-	X	-	-
	Nylon - Polyamide	80	-	X	-	-
	Polyphenylene oxide/ether	80	-	X	-	-
	Porcelain	80	-	X	-	-
	Stainless steel	80	-	X	-	-
	Polycarbonate	60	-	X	-	-
	Polyester paint	60	-	X	-	O
<b>MPE25PK/K4533</b>						
	Aluminum	80	-	X	-	-
	Galvanized steel	80	-	X	-	-
	Polyester paint	80	-	X	-	-
	Stainless steel	80	-	X	-	-
	Acrylonitrile butadiene styrene	60	-	X	-	-

	Nylon - Polyamide	60	-	X	-	-
	Polycarbonate	60	-	X	-	-
	Polyvinyl chloride	60	-	X	-	-
	Unsaturated polyester - thermoset	60	-	X	-	-
<b>PETW-RM-II</b>						
	Acrylic paint	100	-40	X	-	-
	Alkyd paint	100	-40	X	-	-
	Aluminum	100	-40	X	-	-
	Epoxy paint	100	-40	X	-	-
	Epoxy powder paint	100	-40	X	-	-
	Galvanized steel	100	-40	X	-	-
	Melamine	100	-40	X	-	-
	Nylon - Polyamide	100	-40	X	-	-
	Phenolic - Phenol Formaldehyde	100	-40	X	-	-
	Polycarbonate	100	-40	X	-	-
	Polyester paint	100	-40	X	-	-
	Polyester powder paint	100	-40	X	-	-
	Polyphenylene oxide/ether	100	-40	X	-	-
	Polystyrene	100	-40	X	-	-
	Polyurethane paint	100	-40	X	-	-
	Polyurethane powder paint	100	-40	X	-	-
	Stainless steel	100	-40	X	-	-
	Unsaturated polyester - thermoset	100	-40	X	-	-
	Acrylonitrile butadiene styrene	80	-40	X	-	-
	Polyethylene	80	-40	X	-	-
	Polyvinyl chloride	80	-40	X	-	-
	Polypropylene	60	-40	X	-	-
<b>TE3690/M2</b>						
	Alkyd paint	80	-40	X	-	O
	Aluminum	80	-	X	-	O
	Polyester paint	80	-40	X	-	O
	Polyurethane paint	80	-40	X	-	O
	Zinc	80	-40	X	-	O
	Zinc plated metal with chromate	80	-40	X	-	O
	Acrylic paint	60	-40	X	-	O
	Acrylonitrile butadiene styrene	60	-40	X	-	O
	Nylon - Polyamide	60	-40	X	-	O
	Polycarbonate	60	-40	X	-	O
	Polyphenylene oxide/ether	60	-40	X	-	O
<b>TPO/R10</b>						
	Acrylic paint	80	-29	X	X	G, O
	Alkyd paint	80	-29	X	X	-
	Aluminum	80	-29	X	X	G, O
	Epoxy paint	80	-29	X	X	G, O
	Galvanized steel	80	-29	X	X	G, O
	High density polyethylene	80	-29	X	X	G, O
	Nylon - Polyamide	80	-29	X	X	G, O
	Phenolic - Phenol Formaldehyde	80	-29	X	X	-
	Polyester paint	80	-23	X	X	-
	Polyphenylene oxide/ether	80	-29	X	X	-
	Polypropylene	80	-	X	-	G, O
	Polystyrene	80	-29	X	X	-
	Porcelain	80	-29	X	X	-
	Stainless steel	80	-29	X	X	G
	Acrylonitrile butadiene styrene	60	-29	X	X	G, O
	Polycarbonate	60	-	X	-	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

F1 - Occasional exposure to Fuel Oil No. 1.

F2 - Occasional exposure to Fuel Oil No. 2.

G - Occasional exposure to Gasoline splashing.

O - Occasional exposure to Lubricating Oil.

Marking: Company name and model designation.

Last Updated on 2017-05-05

---

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".